

LUBRICANTS FOR INDUSTRIAL USE

CEPSA TUCAN 250

DESCRIPTION

Lubricant oil formulated with pure, highly refined paraffinic base oils.

PRODUCT APPLICATION

- Recommended for all types of reciprocating steam engine, especially for the lubrication of cylinders working at high temperatures.
- Lubrication of worm gears in low ambient temperatures, on spur or bevel gears where antiwear or extreme pressure properties are not required.

PRODUCT PERFORMANCE

- The product's high water content offers a high safety margin against fire.
- Correct viscosity maintained at high operating temperatures.
- High resistance to water and steam washing, easily separating from the condensate.
- Maintains adequate cylinder cleanliness. Prevents ring sticking.
- Long service life. Reduces maintenance costs.

TYPICAL CHARACTERISTICS

CHARACTERISTIC	ASTM STANDARD	CEPSA TUCAN 250
Density 15°C, kg/l	D-4052	0.920
Flash point V/A, °C	D-92	316
Freezing point, °C	D-97	-6
Viscosity at 40°C, cSt	D-445	678
Viscosity at 100°C, cSt	D-445	34.5
Viscosity index	D-2270	80

HEALTH & SAFETY AND ENVIRONMENT

A Material Safety Data Sheet providing information on product hazards, handling precautions, first aid measures, and relevant environmental data is available for this product in accordance with the applicable legislation.