

ERTOIL UTTO 10W30

DESCRIPTION



10W-30 multi-grade oil formulated for transmissions, hydraulic systems, hydrostatic drives and oil-immersed brake systems used in tractors and agricultural machinery.

Product applications

- High oxidation stability.
- Good antiwear and extreme pressure properties.
- Excellent protection against corrosion and rust.
- High foam formation resistance.
- Excellent fluidity at low temperatures.
- Compatibility with sealing materials.

Product performance

- Reduces the build-up of sludge, lacquer and varnishes.
- High capacity to support heavy loads.
- Perfect lubrication for all work systems.
- Immediate oil circulation upon start-up.
- Eliminates vibrations and screeching in oil-immersed brake systems.

QUALITY LEVELS

• John Deere JDM J20C/D	• CAT TO-2
• CNH MAT 3525 / 3505	• MF CMS 1135, 1141, 1143, 1145
• Allison C3/C4	• API GL-4

TYPICAL CHARACTERISTICS

CHARACTERISTIC	ASTM STANDARD	ERTOIL UTTO 10W30
SAE Grade	J300	10W-30
Density 15°C, g/cc	D-4052	0.8854
Freezing point, °C max.	D-5949	-27
Flash point V/A, °C	D-92	214
Viscosity at 100°C, cSt	D-445	9.60
Viscosity at 40°C, cSt	D-445	56.46
Viscosity index	D-2270	155

ENVIRONMENT, HEALTH and SAFETY

A Material Safety Data Sheet providing information on product hazards, handling precautions, first aid measures, and relevant environmental data is available for this product in accordance with the applicable legislation.