

# CEPSA MOTO GRASA CADENAS

### Description



Lubricant grease formulated with polymers in long-life mineral oil, with adherence and extreme pressure additives. The product is packaged in an aerosol.

#### **Applications**

- Product specially prepared for external lubrication of motorcycle transmission chains.
- Shake the container and spray directly onto the element to be lubricated.

#### **Product performance**

- Great adherence.
- Extends drive chain life.
- o Good antirust and anticorrosion protection.
- Superb penetration capability.

### Typical Characteristics

CHARACTERISTIC	UNITS	METHOD	CEPSA MOTO GRASA CADENAS
Appearance		Visual	Semi-fluid liquid
Density at 15 °C	g/ml	ASTM D-4052	0.89
Viscosity at 20 °C	сР	-	7000
Flash point	oC	ASTM D-92	> 260
Corrosion test	hours	ASTM B-117	> 6
E.P. 4-Balls. Weld load (10 s / 1800 rpm)	Kg	ASTM D-2596	>160 Kg

## Environment, Health and Safety

A Material Safety Data Sheet providing information on product hazards, handling precautions, first aid measures, and relevant environmental data is available for this product as per applicable legislation.

The typical values of the characteristics appearing in the table are average values given for guidance purposes only and do not constitute a guarantee. These values may be modified without any prior warning.